

SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of:
US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS
2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous
Products Regulation (HPR)

Revision Date 22-Jan-2024

Revision Number 1

1. Identification

Product identifier

Product Name CND PLEXIGEL PROTECTOR TOP COAT

Other means of identification

Product Code(s) 4708770001

UN-No UN1263

Brand CND
Category Nail
Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use No information available

Restrictions on use No information available

Details of the supplier of the safety data sheet

Initial supplier identifier
Revlon Research Center

Supplier Address
2121 Route 27 Edison, NJ 08818

Emergency telephone number

Emergency Telephone Number INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. Hazard(s) identification

Classification

Flammable liquids	Category 3
Acute toxicity - Inhalation (Vapors)	Category 4
Acute toxicity - Inhalation (Dusts/Mists)	Category 3
Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1

Label elements



Danger**Hazard statements**

Flammable liquid and vapor
 Toxic if inhaled
 Harmful if inhaled
 Causes serious eye irritation
 May cause an allergic skin reaction

Precautionary Statements - Prevention

Avoid breathing dust, fume, gas, mist, vapors and spray
 Use only outdoors or in a well-ventilated area
 Wash face, hands and any exposed skin thoroughly after handling
 Contaminated work clothing must not be allowed out of the workplace
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground and bond container and receiving equipment
 Use explosion-proof electrical, ventilating, lighting and .? equipment
 Use only non-sparking tools
 Take action to prevent static discharges
 Wear protective gloves, eye protection and face protection
 Keep cool

Precautionary Statements - Response

Specific treatment (see .? on this label)

Eyes

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 If eye irritation persists: Get medical advice and attention

Skin

If skin irritation or rash occurs: Get medical advice and attention
 Wash contaminated clothing before reuse
 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water and then shower

Inhalation

IF INHALED: Remove person to fresh air and keep comfortable for breathing
 Call a POISON CENTER or doctor

Fire

In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage

Store in a well-ventilated place. Keep container tightly closed
 Store locked up

Precautionary Statements - Disposal

Dispose of contents and container to an approved waste disposal plant

Unknown acute toxicity**Other information**

May cause long lasting harmful effects to aquatic life.

3. Composition/information on ingredients**Substance**

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Ethyl acetate 141-78-6 (<10)	141-78-6	<10	-	-
Di-HEMA Trimethylhexyl Dicarbamate 72869-86-4 (<10)	72869-86-4	<10	-	-
Butyl Acetate	123-86-4	<10	-	-

123-86-4 (<10)				
Ethyl Trimethylbenzoyl Phenylphosphinate 84434-11-7 (<5)	84434-11-7	<5	-	-
Bis-Trimethylbenzoyl Phenylphosphine Oxide 162881-26-7 (<1)	162881-26-7	<1	-	-

4. First-aid measures

Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. Immediate medical attention is required.
Inhalation	Remove to fresh air. If breathing has stopped, give artificial respiration. Get medical attention immediately. Immediate medical attention is required. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. If breathing is difficult, (trained personnel should) give oxygen. If symptoms persist, call a physician.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.
Skin contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a physician.
Ingestion	Rinse mouth. Never give anything by mouth to an unconscious person. Do NOT induce vomiting. Call a physician or poison control center immediately.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; give artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Do not breathe vapor or mist.

Most important symptoms and effects, both acute and delayed

Symptoms	Itching. Rashes. Hives. May cause redness and tearing of the eyes. Burning sensation. Coughing and/ or wheezing. Difficulty in breathing.
Effects of Exposure	No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians	May cause sensitization in susceptible persons. Treat symptomatically.
---------------------------	--

5. Fire-fighting measures

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire

extinguishing water must be disposed of in accordance with local regulations. Product is or contains a sensitizer. May cause sensitization by skin contact.

Explosion Data

Sensitivity to mechanical impact None.

Sensitivity to static discharge Yes.

Special protective equipment and precautions for fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures**Personal precautions, protective equipment and emergency procedures****Personal precautions**

Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material. Do not breathe vapor or mist. Avoid breathing vapors or mists.

Other information

Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

Methods and material for containment and cleaning up**Methods for containment**

Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Methods for cleaning up

Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. Handling and storage**Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Do not breathe vapor or mist. Handle product only in closed system or provide appropriate exhaust ventilation.

Conditions for safe storage, including any incompatibilities**Storage Conditions**

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store locked up. Keep out of the reach of children.

8. Exposure controls/personal protection**Control parameters****Exposure Limits**

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
ETHYL ACETATE	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
Butyl Acetate	STEL: 150 ppm TWA: 50 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³

Chemical name	Alberta	British Columbia	Ontario	Quebec
ETHYL ACETATE	TWA: 400 ppm TWA: 1440 mg/m ³	TWA: 150 ppm	TWA: 400 ppm	TWA: 400 ppm TWA: 1440 mg/m ³
Butyl Acetate	TWA: 150 ppm TWA: 713 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm

Chemical name	Manitoba	New Brunswick	Newfoundland and Labrador	Nova Scotia
Ethyl acetate 141-78-6 (<10)	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm	TWA: 400 ppm
Butyl Acetate 123-86-4 (<10)	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 50 ppm STEL: 150 ppm

Chemical name	Nunavut	Prince Edward Island	Saskatchewan	Yukon
Ethyl acetate 141-78-6 (<10)	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm	TWA: 400 ppm STEL: 500 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ STEL: 400 ppm STEL: 1400 mg/m ³
Butyl Acetate 123-86-4 (<10)	TWA: 150 ppm STEL: 200 ppm	TWA: 50 ppm STEL: 150 ppm	TWA: 150 ppm STEL: 200 ppm	TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³

Appropriate engineering controls**Engineering controls**

Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Tight sealing safety goggles.

Hand protection

Wear suitable gloves. Impervious gloves.

Skin and body protection	Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.
Respiratory protection	No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Do not breathe vapor or mist. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Clear to translucent
Color	Blue
Odor	Typical
Odor Threshold	No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting / freezing point	No data available	None known
Boiling point / boiling range	No data available	None known
Flash Point	48 °C / 118.4 °F	None known
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	No information available
Flammability Limit in Air		None known
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	1.09	None known
Water solubility	Insoluble in water	None known
Solubility in other solvents	No data available	None known
Partition coefficient: n-octanol/water	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	Approximately 1040 cPs	None known

Other information

Explosive properties	No information available
Oxidizing properties	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC content	No information available
Liquid Density	No information available
Bulk Density	No information available

10. Stability and reactivity

Reactivity	No information available.
-------------------	---------------------------

Chemical stability	Stable under ambient conditions when stored properly (See Section 7, Storage and Handling).
Possibility of hazardous reactions	None under normal processing.
Hazardous Polymerization Conditions to avoid	May occur, if exposed to extremely high temperatures Keep away from strong oxidizers, heat, sparks, open flame and sources of ignition.
Incompatible materials	This product is incompatible with alkaline metals, strong oxidizers (e.g., peroxides, superoxides), strong acids (e.g., hydrochloric or muriatic acids), or strong bases (e.g., lye, potassium hydroxide).
Hazardous decomposition products	If exposed to extremely high temperatures, the product of thermal decomposition may include irritating vapors and carbon oxide gases (e.g., CO, CO ₂)
Hazardous decomposition products	

11. Toxicological information

Information on likely routes of exposure

Product Information

Inhalation	Specific test data for the substance or mixture is not available. May cause irritation of respiratory tract. Toxic by inhalation. (based on components). Harmful by inhalation.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	May cause sensitization by skin contact. Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause irritation. Prolonged contact may cause redness and irritation. May be harmful in contact with skin.
Ingestion	Specific test data for the substance or mixture is not available. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Itching. Rashes. Hives. May cause redness and tearing of the eyes. Coughing and/ or wheezing. Difficulty in breathing.

Acute toxicity Toxic by inhalation. Harmful by inhalation.

Numerical measures of toxicity

Unknown acute toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
ETHYL ACETATE	= 5620 mg/kg (Rat)	> 18000 mg/kg (Rabbit)	= 4000 ppm (Rat) 4 h
DI-HEMA TRIMETHYLHEXYL DICARBAMATE	-	> 2000 mg/kg (Rat)	
Butyl Acetate	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 0.74 mg/L (Rat) 4 h
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rat)	

BIS-TRIMETHYLBENZOYL PHENYLPHOSPHINE OXIDE	> 2000 mg/kg (Rat)	> 2000 mg/kg (Rat)	
--	----------------------	----------------------	--

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	May cause skin irritation.
Serious eye damage/eye irritation	Classification based on data available for ingredients. Causes serious eye irritation.
Respiratory or skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No information available.
Carcinogenicity	No information available.
Reproductive toxicity	No information available.
STOT - single exposure	No information available.
STOT - repeated exposure	No information available.
Aspiration hazard	No information available.

12. Ecological information

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
ETHYL ACETATE	-	LC50: 220 - 250mg/L (96h, Pimephales promelas) LC50: =484mg/L (96h, Oncorhynchus mykiss) LC50: 352 - 500mg/L (96h, Oncorhynchus mykiss)	-	EC50: =560mg/L (48h, Daphnia magna)
Butyl Acetate	EC50: =674.7mg/L (72h, Desmodesmus subspicatus)	LC50: =100mg/L (96h, Lepomis macrochirus) LC50: 17 - 19mg/L (96h, Pimephales promelas)	-	-
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	-	LC50: =1.89mg/L (96h, Danio rerio)	-	-
BIS-TRIMETHYLBENZOYL PHENYLPHOSPHINE OXIDE	-	LC50: >90µg/L (96h, Danio rerio)	-	-

Persistence and Degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
ETHYL ACETATE	0.73
Butyl Acetate	2.3
ETHYL TRIMETHYLBENZOYL PHENYLPHOSPHINATE	2.91
BIS-TRIMETHYLBENZOYL PHENYLPHOSPHINE OXIDE	5.8

Other adverse effects No information available.

13. Disposal considerations**Waste treatment methods**

Waste from residues/unused products	Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.
Contaminated packaging	Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers.
US EPA Waste Number	D001.
California waste information	This product contains one or more substances that are listed with the State of California as a hazardous waste.

14. Transport information**DOT**

UN-No	UN1263
Proper Shipping Name	Paint
Transport hazard class(es)	3
Packing Group	III
Description	UN1263, Paint, 3, III
Special Provisions	B1, B52, IB3, T2, TP1, TP29
Emergency Response Guide Number	128

IATA

UN number or ID number	UN1263
Proper Shipping Name	Paint
Transport hazard class(es)	3
Packing group	III
ERG Code	3L
Special Provisions	A3, A72, A192
Description	UN1263, Paint, 3, III

IMDG

UN number or ID number	UN1263
Proper Shipping Name	Paint
Transport hazard class(es)	3
Packing Group	III
EmS-No	F-E, S-E
Special Provisions	163, 223, 955
Description	UN1263, Paint, 3, III, (48°C c.c.)

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture**International Regulations**

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Complies.

Chemical name	CAS No	U.S. Toxic Substances Control Act (TSCA) status	US TSCA inactive/active designation
Ethyl acetate 141-78-6 (<10)	141-78-6	Compliant	Active
Di-HEMA Trimethylhexyl Dicarbamate 72869-86-4 (<10)	72869-86-4	Compliant	Active
Butyl Acetate 123-86-4 (<10)	123-86-4	Compliant	Active
Ethyl Trimethylbenzoyl Phenylphosphinate 84434-11-7 (<5)	84434-11-7		Unknown *
Bis-Trimethylbenzoyl Phenylphosphine Oxide 162881-26-7 (<1)	162881-26-7	Compliant	Active

*Contact supplier for details. One or more substances in this product are either not listed on the US TSCA inventory, listed on the confidential US TSCA inventory or are otherwise exempted from inventory listing requirements

DSL All components are listed either on the DSL or NDSL.
EINECS/ELINCS Contact supplier for inventory compliance status.
ENCS Contact supplier for inventory compliance status.
IECSC Contact supplier for inventory compliance status.
KECL Contact supplier for inventory compliance status.
PICCS Contact supplier for inventory compliance status.
AICS Contact supplier for inventory compliance status.
NZIoC Contact supplier for inventory compliance status.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

NZIoC - New Zealand Inventory of Chemicals

US Federal Regulations**SARA 313**

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Butyl Acetate	5000 lb	-	-	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
ETHYL ACETATE	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ
Butyl Acetate	5000 lb	-	RQ 5000 lb final RQ RQ 2270 kg final RQ

US State Regulations**California Proposition 65**

This product does not require a Prop 65 chemical warning.

U.S. State Right-to-Know Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
ETHYL ACETATE	X	X	X
Butyl Acetate	X	X	X
BHT	X	X	X
P-HYDROXYANISOLE	X	X	X

U.S. EPA Label information**16. Other information**

NFPA	Health hazards 3	Flammability 2	Instability 0	Special hazards -
HMIS	Health hazards 3	Flammability 2	Physical hazards 0	Personal Protection X

Key or legend to abbreviations and acronyms used in the safety data sheet**Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	-	Skin designation

Key literature references and sources for data used to compile the SDS

Agency for Toxic Substances and Disease Registry (ATSDR)
 U.S. Environmental Protection Agency ChemView Database
 European Food Safety Authority (EFSA)
 EPA (Environmental Protection Agency)
 Acute Exposure Guideline Level(s) (AEG L(s))
 U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
 U.S. Environmental Protection Agency High Production Volume Chemicals
 Food Research Journal
 Hazardous Substance Database
 International Uniform Chemical Information Database (IUCLID)
 National Institute of Technology and Evaluation (NITE)

Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
 NIOSH (National Institute for Occupational Safety and Health)
 National Library of Medicine's ChemID Plus (NLM CIP)
 National Library of Medicine's PubMed database (NLM PUBMED)
 National Toxicology Program (NTP)
 New Zealand's Chemical Classification and Information Database (CCID)
 Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
 Organization for Economic Co-operation and Development High Production Volume Chemicals Program
 Organization for Economic Co-operation and Development Screening Information Data Set
 World Health Organization

Revision Date 22-Jan-2024

Revision Note No information available.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

North America SDS version information - NGHS

UL release:
 GHS Revision 3
 2023 Q1

North America

Full process, including GHS and Transportation Wizards

Chemical name	RCRA - U Series Wastes	RCRA - P Series Wastes
ETHYL ACETATE	U112	-
Chemical name	California Hazardous Waste Status	
ETHYL ACETATE	Toxic Ignitable	
Butyl Acetate	Toxic	